



YARD FORCE

LAWN MOWER



2026

WALK-BEHIND | RIDER | ROBOT



YARD FORCE®



WALK-BEHIND MOWER 01

RIDING MOWER 07

ROBOT MOWER 09

WALK-BEHIND MOWER

Gas Lawn Mower

21"



22"



22"



30"



Cordless Lawn Mower

58V





SELF-PROPELLED REAR WHEEL DRIVE FOR EASIER MOWING WITH LESS EFFORT.

RELIABLE BRIGGS & STRATTON 150CC ENGINE

EQUIPPED WITH DURABLE GT TRANSMISSION.

INTEGRATED MULCH PLUG FOR QUICK AND EASY MULCHING WITHOUT TOOLS.


7-POSITION WHEEL LEVER HEIGHT ADJUSTMENT: 1.25" – 3.75"

22" STEEL DECK FOR DURABILITY SEASON AFTER SEASON.

YF22-3N1SP2V



Integrated Mulch Plug



Striping Technology



Deck Wash Port

Gas Lawn Mower



Model No.	YF21-SD-TW	YF21-SD	YF22-2N1
Technical Specification			
Engine	Briggs & Stratton, 125 cc	Briggs & Stratton, 125 cc	Briggs & Stratton, 125 cc
Lawn Mower Type	Push	Push	Push
Discharge	Side discharge	Side discharge	Side discharge/Mulching(2-in-1)
Deck Size	21" steel	21" steel	22" steel
Cutting Height	1.25"-3.25", 3 positions, individual threaded adjustment	1.25"-3.25", 3 positions, individual height adjustment	1.25"-3.75", 5 positions,
Wheel Size	7"/7", PVC wrapped	7"/7", PVC wrapped	11"/7", PVC wrapped



Gas Lawn Mower



Model No.	YF22-3N1	YF22-3N1SP	YF22-3N1SPF
Technical Specification			
Engine	Briggs & Stratton, 140 cc	Briggs & Stratton, 150 cc	Briggs & Stratton, 150 cc
Lawn Mower Type	Push	Self-propelled(SP)	Self-propelled(SP), FWD
Discharge	Bagging/Side discharge/Mulching (3-in-1)	Bagging/Rear dischargeMulching (3-in-1)	Bagging/Side discharge/Mulching (3-in-1)
Deck Size	22" steel	22" steel	22" steel
Cutting Width	21"	21"	21"
Cutting Height	1.25"-3.75", 7 positions, central height adjustment	1.25"-3.75", 7 positions, central height adjustment	1.25"-3.75", 7 positions, central height adjustment
Wheel Size	8"/8", PVC wrapped, ball bearing	8"/12", PVC wrapped, ball bearing	8"/8", PVC wrapped ball bearing
Grass Bag Capacity	2 bushels	2 bushels	2 bushels



Model No.	YF22-3N1SP2	YF22-3N1SP2V	YF22-3N1SPV
Technical Specification			
Engine	Briggs & Stratton, 150 cc	Briggs & Stratton, 150 cc	Briggs & Stratton, 150 cc
Lawn Mower Type	Self-propelled, RWD	Self-propelled, RWD	Self-propelled, RWD
Discharge	Bagging/side discharge/mulching (3-in-1)	Bagging/side discharge/mulching (3-in-1)	Bagging/side discharge/mulching (3-in-1)
Deck Size	21"	21"	21"
Cutting Height	1.25"-3.75", 6 positions, front and rear wheel linkage	1.25"-3.75", 6 positions, front and rear wheel linkage	1.25"-3.75", 6 positions, front and rear wheel linkage
Handle	Two-level height adjustment	/	Two-level height adjustment
Wheel Size	8"/10", PVC wrapped	8"/10", PVC wrapped	8"/10", PVC wrapped
Mulching Plug	Yes, integrated	Yes, integrated	Yes, integrated
Washport	Optional	Optional	Optional
Grass Bag Capacity	1.7 bushels	1.7 bushels	1.7 bushels

Gas Lawn Mower



**BIG POWERFUL
BRIGGS & STRATTON
223CC OHV ENGINE
DELIVERING 10 FT-LBS.
OF TORQUE***

VARIABLE SPEED UP TO 3.5 MPH



**PEDAL FOR QUICK STOW
HANDLE
ALLOWS FOR EASY,
COMPACT STORAGE WITH
TWO CONVENIENT STORAGE
POSITIONS**



**ADJUSTABLE
CUTTING HEIGHT
1.25" TO 4.25"
(7 SETTINGS)**

WASH PORT

**30 IN DURABLE DECK
MAKE YOUR JOB EASIER
BY CUTTING A WIDER
PATH**



Model No.	YF30-3N1-SPV
------------------	---------------------

Technical Specification	
Engine	Briggs & Stratton, 223 cc
Function	Bagging/side discharge/mulching (3-in-1)
Blade Stop	Blade Brake System (BBS)
Cutting Width	30", dual-blade
Lawn Mower Type	Self-propelled, smart pace
Cutting Height	1.25"–4.25", 7 positions
Wheel Size	8"/10", PVC wrapped, ball bearing
Grass Bag Capacity	2.5 bushels

Walk-Behind String Trimmer



Model No.	YF22-HWT-E
Technical Specification	
Engine	170 cc OHV
Cutting Swath	22"
Cutting Height	2"– 4", adjustable
Trimming Line Dia.	0.155"
Wheel Size	14", PVC wrapped
Handle	Fold-down for easy storage
Assembly	Easy to assemble

58V Built-in Battery Lawn Mower



Model No.	YF58VRXL21SP
Technical Specification	
Battery	58V, 8.6Ah, Li-ion, Integrated
Motor	Brushless
Cutting Width	21"
Cutting Height	0.98"–2.95", 7 positions
Runtime	90–152 min
Coverage	1/3–2/3 acre
Charging Time	30 min



Smart Vertical storage



Top Rated Deck Air Flow



Floating Pack Structure



Smooth Deck, Strong Air Flow

Zero Turn Battery Powered ZTR


Model No.	Z42-562
------------------	----------------

Technical Specification	
Battery	56V, 100Ah, Li-ion
Cutting Width	42"
Cutting Height	1.5"-4.5", 10 positions
Speed	3/5/6/7 mph forward, 3 mph reverse
Tires	11"/18"
Features	5" LCD, LED headlights, USB port, Adjustable suspension seat, Rear hitch, Storage compartment
Coverage	Up to 4 acres
Bagging Kit	Optional

Riding Lawn Mower


Model No.	YF56vRX-RER38 Li50
------------------	---------------------------

Technical Specification	
Battery	56V, 50Ah
Cutting Width	38"
Cutting Height	1.5"–4.5", 12 positions
Speed	8 mph (driving)/5 mph (mowing), 3 mph reverse
Tires	15"/16"
Features	LED light, Cruise button, LCD
Coverage	Up to 2 acres
Bagging Kit	Optional

ROBOTIC MOWER



20V

NEW



NEW



28V



Robotic Mower


Model No.	YF-i600	Revola iVR16
Technical Specification		
Battery	20V, 2.5Ah, Lithium integrated	20V, 8Ah, Lithium integrated
Cutting Width	7"	7"
Runtime	Up to 90 min	Up to 90 min
Navigation	Boundary-free, AI camera	Boundary-free, Satellite positioning, AI camera
Slope Capability	Up to 30°	Up to 30°
Control	APP control, Wi-Fi/Bluetooth	APP control, Wi-Fi/Bluetooth
Sensors	Bump sensor, Rain sensor	Bump sensor, Rain sensor, Lift/Flip collision
Coverage	Less than 1/4 acre	Less than 1/2 acre



Model No.	NX100i	Revola X4E
Technical Specification		
Battery	28V, 2.9Ah, Lithium integrated	28V, 4.0Ah, Lithium integrated
Cutting Width	7"	9"
Runtime	Up to 90 min	Up to 120 min
Navigation	Boundary wire guided, Multi-zone	Boundary wire guided, Multi-zone
Slope Capability	Up to 22°	Up to 22°
Control	APP control, WiFi	APP control, WiFi
Sensors	Obstacle sensor, Lift sensor, Tilt sensor, Rain sensor	Obstacle sensor, Lift sensor, Tilt sensor, Rain sensor
Coverage	Up to 1/3 acre	Up to 1/2 acre



Yard Force Power Equipment

Address: 3655 Kennesaw North Industrial Pkw,
Kennesaw, GA 30144.

Factory & Distribute Center.
Address: 158 E. Parrish Street, Statesboro, GA 30458.

Email: support@MerotecUSA.com

MEROTEC GmbH

Address: Otto-Brenner-Str. 8, 47877 Willich, Germany

Email: sales@merotec.eu

SUMEC UK

Address: UnitA & B, Escrick Business Park, Escrick, York, YO19 6FD,
United Kingdom

Email: sales@sumec-uk.com

MEROTEC AUSTRALIA

Address: Suite 3, 130-134 Pacific Hwy, Greenwich, NSW, 2065, Australia

Email: peter@sumec.net.au

SUMEC FRANCE

Address: 59 Bis Rue Du Murier 37540 Saint-Cyr-Sur-Loire, France

Email: contact@sumec-fr.com